

## TRAC FARM PLUS - Specificații tehnice



### Descriere

TRAC FARM PLUS este o anvelopă spate pentru tractor concepută special pentru aplicații de cultivare a solului și de transport. Anvelopa are benzi de rulare mai adânci cu caneluri cu unghi dublu pentru a asigura atât o tracțiune excelentă, cât și o deplasare confortabilă pe șosea. Designul special al benzii de rulare oferă mai mult contact pentru o stabilitate mai bună și proprietăți excelente de auto-curățare. TRAC FARM PLUS asigură un ciclu de viață mai lung al anvelopei.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	16.9 - 30
LI/SS	144 A6

## Dimensiuni Standard internațional

Rating de sarcină	12
Lățimea secțiunii (mm)	440
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	679
Rolling Circumference (mm)	4466
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004529
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.40
30	2800

Imprimat pe 4/20/2024 5:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..