

## TRAC FARM - Specificații tehnice



### Descriere

TRAC FARM este o anvelopă pentru sarcini grele concepută special pentru tractoare în aplicații de cultivare a solului și de transport. Banda de rulare adâncă și compusul special rezistent la tăieturi și așchii fac ca anvelopa să fie potrivită pentru cele mai dificile condiții de funcționare, asigurând cea mai bună rentabilitate a investiției pe parcursul întregului ciclu de viață al produsului. TRAC FARM a fost proiectată cu mai multe caneluri, oferind proprietăți extraordinare de tracțiune și auto-curățare.

### UM

Standard internațional

### Construcție

 BIAS

### Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	12.4 - 28
LI/SS	125 A6

## Dimensiuni Standard internațional

Rating de sarcină	12
Lățimea secțiunii (mm)	320
Overall Diameter (mm)	1295
Static Loaded Radius (mm)	602
Rolling Circumference (mm)	3890
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E11-106R-003562
TRA Code	R1

## Load capacity (Kg)

km/h / bar	2.50
30	1650

Imprimat pe 4/26/2024 10:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..