

TRAC FARM - Specificații tehnice



Descriere

TRAC FARM este o anvelopă pentru sarcini grele concepută special pentru tractoare în aplicații de cultivare a solului și de transport. Banda de rulare adâncă și compusul special rezistent la tăieturi și așchii fac ca anvelopa să fie potrivită pentru cele mai dificile condiții de funcționare, asigurând cea mai bună rentabilitate a investiției pe parcursul întregului ciclu de viață al produsului. TRAC FARM a fost proiectată cu mai multe caneluri, oferind proprietăți extraordinare de tracțiune și auto-curățare.

UM

Standard internațional

Construcție

 BIAS

Mașinării

Agricultură: Tractor

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	13.6 - 28
LI/SS	128 A6

Dimensiuni Standard internațional

Rating de sarcină	12
Lățimea secțiunii (mm)	365
Overall Diameter (mm)	1345
Static Loaded Radius (mm)	625
Rolling Circumference (mm)	4034
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-003572
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.30
30	1800

Imprimat pe 4/26/2024 8:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..