

TRAC SUPER - Specificații tehnice



Descriere

TRAC SUPER este prima anvelopă radială introdusă în segmentul municipal al BKT' Structura anvelopei cu bandă din oțel asigură o deplasare excelentă, combinată cu cea mai bună performanță de tracțiune. Drept urmare, este potrivită în special pentru aplicații pe suprafețe mari de gazon, cum ar fi parcuri și marginea drumurilor.

UM

US Standard

Construcție

 RADIAL

Mașinării

Agricultură: Tractor mic

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	400/50 R 15
LI/SS	118 A8/B

Dimensiuni US Standard

Usa code	94075300
Lățimea secțiunii (inch)	15
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	13
Rolling Circumference (inch)	89.3
Rim Rec	13.00
ECE	E11-106R-009073

Load capacity (lbs)

mph / psi	12	17	23
30	1870	2400	2910
25	1870	2400	2910
20	2100	2680	3270
10	2360	3030	3680
5	2620	3360	4080

Imprimat pe 4/25/2024 4:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..