

## XL GRIP (ADT) - Specificații tehnice



### Descriere

XL GRIP (ADT) este o anvelopă cu o cută înclinată pentru basculante articulate, concepută pentru a minimiza tăieturile și perforările în condiții severe în care este necesară o tracțiune excepțională. Aceste caracteristici asigură o durată de viață extinsă a anvelopei.

### UM

US Standard

### Construcție

✚ BIAS

### Mașinării

OTR: Basculantă articulată (ADT)

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	26.5 - 25

## Dimensiuni US Standard

Usa code	94057870
Rating de sarcină	32
Overall Width (inch)	26.8
Overall Diameter (inch)	68.5
Static Loaded Radius (inch)	31.3
Rolling Circumference (inch)	202.8
Rim Rec	22.00/3.0
TRA Code	E3
Tread Depth	46

## Load capacity (lbs)

mph / psi	62
30	24690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/11/2025 3:09 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..