

XL GRIP (ADT) - Specificații tehnice



Descriere

XL GRIP (ADT) este o anvelopă cu o cută înclinată pentru basculante articulate, concepută pentru a minimiza tăieturile și perforările în condiții severe în care este necesară o tracțiune excepțională. Aceste caracteristici asigură o durată de viață extinsă a anvelopei.

UM

US Standard

Construcție

 BIAS

Mașinării

OTR: Basculantă articulată (ADT)

| | |
|-----------------------|-----------|
| Versiune | STANDARD |
| Tip | TL |
| Dimensiunea anvelopei | 29.5 - 25 |

Dimensiuni US Standard

| | |
|------------------------------|-----------|
| Usa code | 94057887 |
| Rating de sarcină | 28 |
| Overall Width (inch) | 29.9 |
| Overall Diameter (inch) | 73.2 |
| Static Loaded Radius (inch) | 33.4 |
| Rolling Circumference (inch) | 218.3 |
| Rim Rec | 25.00/3.5 |
| TRA Code | E3 |

Load capacity (lbs)

| | |
|-----------|-------|
| mph / psi | 47 |
| 30 | 25400 |

Imprimat pe 4/26/2024 5:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..