

SIZE	Version	LI/SS	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
9.00 - 16	STANDARD	137 A6		16	6.50 H	6.00 G	260	910	0	0	TT
9.00 - 16	STANDARD	132 A6		12	6.50 H	6.00 G	260	910	0	0	TT
12.5/80 - 18	STANDARD		142 A8	12	W 9	11	305	980	0	0	TT
12.5/80 - 18	STANDARD		142 A8	12	W 9	11	305	980	0	0	TL
12.5/80 - 18	STANDARD		148 A8	16	W 9	11	305	980	0	0	TT
10.00 - 20	ARAMID + STEEL BELTED			18	7.5	7.0	285	1075	505	3257	TT
10.00 - 20	ARAMID BELTED			18	7.5	7.0	285	1075	505	3257	TT
10.00 - 20	INDUSTRIAL			18	7.5	7.0	285	1075	505	3257	TT
10.00 - 20	STEEL BELTED			18	7.5	7.0	285	1075	505	3257	TT
12.00 - 20	INDUSTRIAL			20	8.5	8.0	320	1155	545	3465	TT
12.00 - 24	INDUSTRIAL			20	8.5	8.0	320	1250	585	3710	TT
14.9 - 24	INDUSTRIAL	145 A8		12	DW 13	DW 11 ; DW 12 ; DW 13L	380	1240	575	3646	TT
16.9 - 28	INDUSTRIAL	152 A8		12	DW 15L	DW 14L	450	1400	640	4175	TT

Imprimat pe 4/20/2024 7:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..