

# XL GRIP (E3) - Specificații tehnice



### **Descriere**

XL GRIP (E-3) este o anvelopă cu pliuri înclinate pentru basculante rigide, concepută pentru a minimiza tăieturile și perforările în condiții severe în care este necesară o tracțiune excepțională. Aceste caracteristici au ca rezultat o durată de viață extinsă a anvelopei.

#### UM

**US Standard** 

## Construcție



# Mașinării

OTR: Autobasculantă rigidă

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	18.00 - 33

# **Dimensiuni US Standard**

Usa code	94015818
Rating de sarcin <b>ă</b>	36
Overall Width (inch)	20.1
Overall Diameter (inch)	71.7
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	212
Rim Rec	13.00/2.5
TRA Code	E3
Tread Depth	40

# Load capacity (lbs)

mph / psi	94	123
30	24700	-
5	-	40800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Imprimat pe 5/10/2025 11:34 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..