

XL GRIP (L3) - Specificații tehnice



Descriere

XL GRIP (E-3/L-3) este o anvelopă cu cută înclinată cu bază lată pentru încărcătoare, concepută pentru a minimiza tăieturile și perforările în aplicațiile de încărcare dificile. Oferă tracțiune excepțională, precum și o durată de viață extinsă a anvelopei.

UM

US Standard

Construcție

BIAS

Mașinării

Industrial: Încărcător

OTR: Buldozer • Încărcător

Versiune	STANDARD
Tip	TL
Dimensiunea anvelopei	23.5 - 25

Dimensiuni US Standard

Usa code	94015894
Rating de sarcină	24
Overall Width (inch)	23.6
Overall Diameter (inch)	64
Static Loaded Radius (inch)	29.2
Rolling Circumference (inch)	189.4
Rim Rec	19.50/2.5
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	51	69
30	17600	-
5	-	27600

Imprimat pe 4/27/2024 10:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..