

## XL GRIP PLUS - Specificații tehnice



### Descriere

XL GRIP PLUS (L-4) a fost special concepută pentru încărcătoare. Banda de rulare adâncă oferă rezistență ridicată la tăiere și la perforare, precum și un ciclu de viață extins al anvelopei. XL GRIP PLUS este potrivită în special pentru lucrări în condiții dificile. &nbsp; &nbsp; &nbsp;

### UM

Standard internațional

### Construcție

✚ BIAS

### Mașinării

OTR: Buldozer • Încăcător

|                       |            |
|-----------------------|------------|
| Versiune              | STANDARD   |
| Tip                   | TL         |
| Dimensiunea anvelopei | 35/65 - 33 |

## Dimensiuni Standard internațional

|                       |           |
|-----------------------|-----------|
| Rating de sarcină     | 42        |
| Overall Width (mm)    | 900       |
| Overall Diameter (mm) | 2080      |
| Rim Rec               | 28.00/3.5 |
| TRA Code              | L4        |

## Load capacity (Kg)

| km/h / bar | 6.25  |
|------------|-------|
| 10         | 26500 |

Imprimat pe 4/27/2024 6:17 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..