

XL GRIP (T) - Specificații tehnice



Descriere

XL GRIP (E-3) se potrivește cel mai bine camioanelor de încărcare/descărcare care transportă sarcini grele în aplicații miniere. Compusul benzii de rulare este proiectat pentru a minimiza tăieturile și perforările pe cele mai dificile terenuri. XL GRIP (E-3) oferă o tracțiune excepțională și un ciclu de viață extins al anvelopei.

UM

Standard internațional

Construcție

 BIAS

Mașinării

OTR: Camion On/Off

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	12.00 - 20

Dimensiuni Standard internațional

Rating de sarcină	24
Overall Width (mm)	320
Overall Diameter (mm)	1155
Static Loaded Radius (mm)	545
Rolling Circumference (mm)	3465
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.90
90 LS/LD	3550

Imprimat pe 4/26/2024 4:03 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..