



XL GRIP (T) - Specificații tehnice



Descriere

XL GRIP (E-3) se potrivește cel mai bine camioanelor de încărcare/descărcare care transportă sarcini grele în aplicații miniere. Compusul benzii de rulare este proiectat pentru a minimiza tăieturile și perforările pe cele mai dificile terenuri. XL GRIP (E-3) oferă o tracțiune excepțională și un ciclu de viață extins al anvelopei.

UM

US Standard

Construcție

❖ BIAS

Mașinării

OTR: Camion On/Off

Versiune	STANDARD
Tip	TT
Dimensiunea anvelopei	12.00 - 24

Dimensiuni US Standard

Usa code	94031122
Rating de sarcină	24
Overall Width (inch)	12.6
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	146.1
Rim Rec	8.5
Rim Alt	8.0
Tread Depth	30

Load capacity (lbs)

mph / psi	119
50 LS/LD	8730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Imprimat pe 5/10/2025 3:35 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..