

XL GRIP ULTRA - Specificații tehnice



Descriere

XL GRIP ULTRA este o anvelopă cu pliuri înclinate, potrivită în special pentru camioanele de încărcare/descărcare în condiții de lucru grele, cum ar fi aplicații miniere, cariere și șantiere de construcții. Designul nedirecțional al benzii de rulare oferă o tracțiune excelentă pe față și laterală. Anvelopa are o carcasă puternică din nailon, cu bare de legătură optimizate și un compus special al benzii de rulare pentru a asigura rezistență ridicată la tăiere și perforare, precum și o durabilitate excelentă și rezistență la uzură, pe lângă cele mai bune proprietăți de auto-curățare chiar și pe suprafețe stâncoase.

UM

US Standard

Construcție

 BIAS

Mașinării

OTR: Camion On/Off

Versiune	INDUSTRIAL
Tip	TT
Dimensiunea anvelopei	12.00 - 24

Dimensiuni US Standard

Usa code	94060856
Rating de sarcină	24
Overall Width (inch)	12.6
Overall Diameter (inch)	49.2
Static Loaded Radius (inch)	23
Rolling Circumference (inch)	146.1
Rim Rec	8.5
Rim Alt	8.0

Load capacity (lbs)

mph / psi	119
30 LS/LD	9520

Imprimat pe 4/28/2024 2:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..