

AGRIMAX FORCE - Технические спецификации



Description

AGRIMAX FORCE — это радиальные шины премиум-класса от компании BKT, разработанные специально для подготовки почвы, грузоперевозок и уборки урожая на высокомошных тракторах и обеспечивающие максимальные показатели производительности и эффективности. Благодаря технологии IF эти шины при пониженном давлении воздуха способны выдерживать большую нагрузку по сравнению со стандартными шинами. При этом они снижают уплотнение почвы. AGRIMAX FORCE имеет усиленный борт и обеспечивает улучшенную тягу, великолепные способности к самоочищению, снижение расхода топлива и комфортное движение.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Комбайн • Трактор высокой мощности

| | |
|-----------|--------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | IF 650/75 R 38 CFO |
| LI/SS | 175 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94069477 |
| Section Width (inch) | 25.6 |
| Overall Diameter (inch) | 76.4 |
| Static Loaded Radius (inch) | 34.1 |
| Rolling Circumference (inch) | 228.4 |
| Rim Rec | DW 23 B |
| Rim Alt | DW 21 B |
| ECE | E11-106R-007385 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 6520 | 7490 | 8590 | 9700 | 10810 | 11920 | 13020 | 13850 |
| From 40 to 25 | 7160 | 8230 | 9440 | 10650 | 11880 | 13090 | 14310 | 15220 |
| 20 | 7450 | 8560 | 9830 | 11090 | 12360 | 13620 | 14890 | 15830 |
| 12 | 7730 | 8890 | 10200 | 11510 | 12820 | 14150 | 15460 | 16440 |
| 5 | 9090 | 10440 | 11990 | 13540 | 15080 | 16630 | 18170 | 19330 |
| Upto 20 Cyc | 9310 | 10690 | 12270 | 13850 | 15440 | 17010 | 18600 | 19780 |
| Upto 10 Cyc | 11090 | 12750 | 14630 | 16520 | 18400 | 20290 | 22170 | 23580 |
| Upto 5 Cyc | 12160 | 13970 | 16040 | 18110 | 20180 | 22250 | 24320 | 25860 |
| 5 HT | 7450 | 8560 | 9830 | 11090 | 12360 | 13620 | 14890 | 15830 |

Printed on 23.04.2024 10:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..