

## AGRIMAX FORTIS - Технические спецификации



### Description

AGRIMAX FORTIS — ваш надежный партнер в работе по подготовке полей, обработке почвы и грузоперевозкам. Предназначенные для самых последних моделей самых современных и самых мощных тракторов, шины AGRIMAX FORTIS выдерживают очень большие нагрузки, даже на скорости до 65 км/ч. Они обеспечивают превосходную тягу, прекрасную управляемость и наивысший комфорт для истинного удовольствия от вождения. Шина изготовлена с усиленным нейлоновым каркасом для повышения производительности в поле и защиты почвы благодаря ее сниженному уплотнению.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Опрыскиватель

Version	SPECIAL
Type	TL
Tyre Size	710/75 R 42
LI/SS	175 D/172 E

## Dimensions International Standard

Section Width (mm)	716
Overall Diameter (mm)	2133
Static Loaded Radius (mm)	970
Rolling Circumference (mm)	6406
SRI (mm)	1000
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E4-106R-001835
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3025	3530	3970	4410	4855	5230	5800	6300
65	3315	3865	4350	4830	5315	5730	6350	6900
50	3480	4060	4565	5075	5580	6015	6670	7245
40	3630	4235	4765	5295	5825	6275	6960	7560
30	3810	4445	5000	5555	6110	6590	7305	7935
10 LT	4440	5180	5830	6475	7125	7680	8510	9250
10 HT	3810	4445	5000	5555	6110	6590	7305	7935

Printed on 27.04.2024 10:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..