



AGRIMAX FORTIS - Загрузить лист технических данных



Description

AGRIMAX FORTIS — ваш надежный партнер в работе по подготовке полей, обработке почвы и грузоперевозкам. Предназначенные для самых последних моделей самых современных и самых мощных тракторов, шины AGRIMAX FORTIS выдерживают очень большие нагрузки, даже на скорости до 65 км/ч. Они обеспечивают превосходную тягу, прекрасную управляемость и наивысший комфорт для истинного удовольствия от вождения. Шина изготовлена с усиленным нейлоновым каркасом для повышения производительности в поле и защиты почвы благодаря ее сниженному уплотнению.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Опрыскиватель

| SIZE | Version | TRA Code | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|--------------------|----------|----------|--------------|---------|-------------------|-----|------|-----|------|------|------|----------------|
| 600/70 R 30 | SPECIAL | R1W | 158 D/161 A8 | DW 20 B | DW 18 L ; W 18 L | 611 | 1602 | 724 | 4810 | 750 | TL | E4-106R-001400 |
| 600/70 R 30 | STANDARD | R1W | 158 D/161 A8 | DW 20 B | DW 18 L ; W 18 L | 611 | 1602 | 724 | 4810 | 750 | TL | E4-106R-001400 |
| 600/70 R 34 | SPECIAL | R1W | 160 D/163 A8 | DW 18 L | DW 20 B ; W 18 L | 591 | 1704 | 761 | 5109 | 800 | TL | E4-106R-001401 |
| 600/70 R 34 | STANDARD | R1W | 160 D/163 A8 | DW 18 L | DW 20 B ; W 18 L | 591 | 1704 | 761 | 5109 | 800 | TL | E4-106R-001401 |
| 650/85 R 38 | SPECIAL | R1W | 173 D/176 A8 | DW 23 B | DW 21 B ; DW 20 B | 675 | 2071 | 935 | 6184 | 975 | TL | E4-106R-001426 |
| 650/85 R 38 | STANDARD | R1W | 173 D/176 A8 | DW 23 B | DW 21 B ; DW 20 B | 675 | 2071 | 935 | 6184 | 975 | TL | E4-106R-001426 |
| 800/70 R 38 | STANDARD | R1W | 178 D/181 A8 | DW 25 B | DW 27 B | 798 | 2085 | 912 | 6202 | 975 | TL | E4-106R-001424 |
| 710/75 R 42 | SPECIAL | R1W | 175 D/172 E | DW 23 B | DW 25 B | 716 | 2133 | 970 | 6406 | 1000 | TL | E4-106R-001835 |
| 710/75 R 42 | STANDARD | R1W | 175 D/172 E | DW 23 B | DW 25 B | 716 | 2133 | 970 | 6406 | 1000 | TL | E4-106R-001835 |

Printed on 27.04.2024 8:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..