



# AGRIMAX RT 600 - Загрузить лист технических данных

## Description

Шины AGRIMAX RT 600 идеально подойдут для техники, используемой на пастбищах, а также для уборочной техники и разбрасывателей. Благодаря большой площади контакта с поверхностью земли шины AGRIMAX RT 600 обеспечивают отличное распределение давления, снижая повреждение пастбищ и защищая почву. Круглая плечевая зона, усиленный борт и увеличенное количество грунтозацепов гарантируют великолепную устойчивость и отличную тягу.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Сельское хозяйство: Комбайн • Разбрасыватель • Трактор-тягач



SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
<b>620/75 R 26 (23.1 R 26)</b>	STANDARD	167 A8/B	DW 20 B		625	1590	730	4851	750	TL	E11-106R-002993
<b>750/65 R 26</b>	STANDARD	171 A8/B	DW 24 B	DW 23 B ; DW 25 B	750	1636	737	4987	775	TL	E11-106R-006182
<b>750/70 R 26</b>	STANDARD	172 A8/B	DW 25 B	DW 24 B	780	1750	785	5269	825	TL	E11-106R-007934
<b>540/65 R 28</b>	STANDARD	142 D/145 A8	W 16 L	W 18 L	530	1413	642	4202	675	TL	E11-106R-002980
<b>1050/50 R32</b>	STANDARD	184 A8/181 B	36.0 VA		1059	1863	826	5700	875	TL	E4-106R-000813
<b>650/75 R 32</b>	STANDARD	172 A8/B	DW 21 B	DW 20 B ; DW 23 B	655	1789	807	5416	850	TL	E11-106R-004755
<b>800/65 R 32 (30.5L R 32)</b>	STANDARD	176 A8/173 B	DW 27 B	DH 27 B ; DW 25 B	775	1820	823	5558	875	TL	E4-106R-001428
<b>800/65 R 32 (30.5L R 32)</b>	STANDARD	181 A8/178 B	DW 27 B	DH 27 B ; DW 25 B	775	1820	823	5558	875	TL	E4-106R-001429
<b>900/60 R 32</b>	STANDARD	181 A8/178 B	DW 27 B	DW 28 B ; DW 30 B	896	1893	841	5697	900	TL	E11-106R-005768
<b>IF 1250/50 R 32 CFO</b>	STEEL BELTED	201 B	VA44/1.7 (multipiece)		1247	2063	897	6136	975	TL	E11-106R-006958
<b>IF 1250/50 R 32 CFO</b>	STEEL BELTED	201 B	DH44B/1.3 (multipiece)		1247	2063	897	6136	975	TL	E11-106R-006958
<b>IF 680/85 R 32 CFO</b>	STANDARD	179 D	DW23 B	DW21 B	682	1960	846	5860	925	TL	E11-106R-006401
<b>650/65 R 38</b>	STANDARD	157 D/160 A8	DW 20 B		645	1811	833	5443	875	TL	E11-106R-002990
<b>710/70 R 38</b>	STANDARD	178 D/181 A8	DW 23 B	DW 25 B	706	1959	881	5926	925	TL	E11-106R-006178

Printed on 26.04.2024 17:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..