

## AGRIMAX RT 657 - Технические спецификации



### Description

Шины AGRIMAX RT 657 идеально подходят для машин, эксплуатируемых для обработки почвы и для дорожных перевозок; некоторые размеры также предусмотрены для техники, используемой для уборки урожая на виноградных плантациях. Эти шины гарантируют непревзойденный комфорт при движении, а также значительную экономию топлива. Шины характеризуются высокой грузоподъемностью, в том числе и на большой скорости. AGRIMAX RT 657 — лучший выбор для тех, кому нужны надежные универсальные шины с великолепными характеристиками.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Трактор-тягач • Комбайн для уборки винограда

|           |              |
|-----------|--------------|
| Version   | SPECIAL      |
| Type      | TL           |
| Tyre Size | 600/65 R 28  |
| LI/SS     | 154 D/157 A8 |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94066025       |
| Section Width (inch)         | 24.1           |
| Overall Diameter (inch)      | 58.7           |
| Static Loaded Radius (inch)  | 26.4           |
| Rolling Circumference (inch) | 176            |
| Rim Rec                      | DW 20 B        |
| Rim Alt                      | W 18 L         |
| ECE                          | E4-106R-000621 |
| TRA Code                     | R1W            |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20   | 23   | 29    | 35    |
|-----------|------|------|------|------|------|------|-------|-------|
| 40        | 3970 | 4630 | 5210 | 5790 | 6370 | 6870 | 7610  | 8250  |
| 30        | 4180 | 4870 | 5480 | 6080 | 6690 | 7220 | 7990  | 8690  |
| 25        | 4360 | 5090 | 5730 | 6370 | 7010 | 7550 | 8370  | 9090  |
| 20        | 4570 | 5330 | 6000 | 6670 | 7330 | 7900 | 8750  | 9510  |
| 5 LT      | 5320 | 6210 | 6990 | 7760 | 8530 | 9200 | 10200 | 11080 |
| 5 HT      | 4570 | 5330 | 6000 | 6670 | 7330 | 7900 | 8750  | 9510  |

Printed on 02.03.2024 17:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..