

## AGRIMAX RT 855 - Технические спецификации



### Description

Шины AGRIMAX RT 855 обеспечивают превосходную тягу и высокий уровень комфорта. В основном они предназначены для машин, эксплуатируемых для обработки почвы, а также для перевозок как по полю, так и по дорогам. Шины определенных размерностей также подходят для техники, используемой для опрыскивания почвы и уборки урожая на виноградных плантациях. Шины AGRIMAX RT 855 отличаются исключительными свойствами самоочистки, что позволяет использовать их для дорожных перевозок практически сразу же после полевых работ.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Опрыскиватель • Трактор-тягач •  
Комбайн для уборки винограда

Version	STANDARD
Type	TL
Tyre Size	460/85 R 34 (18.4 R 34)
LI/SS	158 A8/B

## Dimensions US Standard

Usa code	94047772
Section Width (inch)	18.7
Overall Diameter (inch)	64.8
Static Loaded Radius (inch)	28.4
Rolling Circumference (inch)	191.5
Rim Rec	W 16 L
Rim Alt	W 14 L ; W 15 L
ECE	E11-106R-006759
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46
30	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
25	3660	4310	4970	5530	6180	6750	7410	7970	8720	9370
20	3910	4620	5320	5920	6620	7230	7930	8530	9340	10030
5 LT	4910	5780	6660	7420	8290	9050	9920	10680	11680	12550
5 HT	4190	4950	5700	6340	7090	7740	8490	9130	9990	10740

Printed on 19.04.2024 3:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..