

AGRIMAX RT 855 - Технические спецификации



Description

Шины AGRIMAX RT 855 обеспечивают превосходную тягу и высокий уровень комфорта. В основном они предназначены для машин, эксплуатируемых для обработки почвы, а также для перевозок как по полю, так и по дорогам. Шины определенных размерностей также подходят для техники, используемой для опрыскивания почвы и уборки урожая на виноградных плантациях. Шины AGRIMAX RT 855 отличаются исключительными свойствами самоочистки, что позволяет использовать их для дорожных перевозок практически сразу же после полевых работ.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Опрыскиватель • Трактор-тягач •
Комбайн для уборки винограда

Version	STANDARD
Type	TL
Tyre Size	520/85 R 46 (20.8 R 46)
LI/SS	173 A8/B

Dimensions US Standard

Usa code	94040544
Section Width (inch)	20.3
Overall Diameter (inch)	80.8
Static Loaded Radius (inch)	38
Rolling Circumference (inch)	248.4
Rim Rec	DW 16 L ; W 16 A ; W 16 L ; DD 16
Rim Alt	DW 18 L ; W 18 L ; W 18 A
ECE	E4-106R-001494
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	35	41	46	52	58
30	5160	6000	6840	7680	8530	9370	10750	11750	12750	13610	14330
25	5160	6000	6840	7680	8530	9370	10750	11750	12750	13610	14330
20	5520	6430	7330	8230	9140	10030	11500	12580	13650	14560	15330
5 LT	6910	8040	9170	10300	11430	12550	14410	15740	17080	18240	19200
5 HT	5520	6430	7330	8230	9140	10030	11500	12580	13650	14560	15330

Printed on 19.04.2024 3:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..