

## AGRIMAX RT 945 - Технические спецификации



### Description

Шины AGRIMAX RT 945 специально разработаны для эксплуатации в сфере обработки пропашных культур: они не повреждают культуры и позволяют собрать максимальный урожай. Шины AGRIMAX RT 945 отличаются исключительными свойствами самоочистки, что позволяет использовать их для дорожных перевозок (где они доказывают свои непревзойденные качества) практически сразу же после полевых работ. Прочный каркас придает шинам превосходную устойчивость, великолепную тягу и исключительный срок службы.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Опрыскиватель • Трактор-тягач

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 320/90 R 46<br>(12.4 R 46) |
| LI/SS     | 148 D/151 A8               |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94051694        |
| Section Width (inch)         | 12.6            |
| Overall Diameter (inch)      | 68.7            |
| Static Loaded Radius (inch)  | 31.9            |
| Rolling Circumference (inch) | 206             |
| Rim Rec                      | W 10            |
| Rim Alt                      | W 9 ; W 11      |
| ECE                          | E11-106R-004068 |
| TRA Code                     | R1W             |

## Load capacity (lbs)

| mph / psi | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52    |
|-----------|------|------|------|------|------|------|------|-------|
| 40        | 2990 | 3890 | 4730 | 5210 | 5490 | 6050 | 6540 | 6940  |
| 30        | 3140 | 4090 | 4970 | 5480 | 5760 | 6350 | 6870 | 7300  |
| 25        | 3270 | 4270 | 5180 | 5710 | 6020 | 6620 | 7150 | 7610  |
| 20        | 3440 | 4480 | 5430 | 5990 | 6300 | 6940 | 7510 | 7980  |
| 5         | 4490 | 5840 | 7090 | 7810 | 8230 | 9070 | 9800 | 10420 |

Printed on 25.04.2024 23:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..