

## AGRIMAX RT 955 - Технические спецификации



### Description

AGRIMAX RT 955 — это радиальные шины компании BKT для техники, используемой для обработки пропашных культур; при этом шины определенных размерностей также подходят для опрыскивания и работ на виноградниках. Специальный рисунок протектора с закругленной плечевой зоной обеспечивает превосходные тяговые характеристики, устойчивость и способность к самоочищению. Благодаря крепкому каркасу шины AGRIMAX RT 955 обладают высокой грузоподъемностью.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Опрыскиватель • Комбайн для уборки винограда

|           |                           |
|-----------|---------------------------|
| Version   | STANDARD                  |
| Type      | TL                        |
| Tyre Size | 230/95 R 36<br>(9.5 R 36) |
| LI/SS     | 130 A8/B                  |

## Dimensions US Standard

|                              |                |
|------------------------------|----------------|
| Usa code                     | 94027477       |
| Section Width (inch)         | 9.4            |
| Overall Diameter (inch)      | 53.2           |
| Static Loaded Radius (inch)  | 25.2           |
| Rolling Circumference (inch) | 161.9          |
| Rim Rec                      | W 8            |
| Rim Alt                      | W 7            |
| ECE                          | E4-106R-000765 |
| TRA Code                     | R1             |

## Load capacity (lbs)

| mph / psi | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 64   |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 30        | 1640 | 2140 | 2600 | 2850 | 3020 | 3320 | 3600 | 3900 | 4180 | -    |
| 25        | 1640 | 2140 | 2600 | 2850 | 3020 | 3320 | 3600 | 3900 | 4180 | -    |
| 20        | 1750 | 2290 | 2790 | 3050 | 3240 | 3550 | 3870 | 4180 | 4490 | -    |
| 5         | 1950 | 2460 | 3020 | 3580 | 4160 | 4280 | 4780 | 5280 | 5790 | 6280 |

Printed on 08.12.2023 7:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..