

AGRIMAX SPARGO - Технические спецификации



Description

AGRIMAX SPARGO — это шины компании BKT для техники, используемой для обработки пропашных культур. Они были созданы, чтобы увеличить производительность при работе в поле и обеспечить защиту почвы. Технология VF наделяет шины повышенной грузоподъемностью при стандартном давлении. Благодаря прочному каркасу и увеличенному количеству грунтозацепов шины AGRIMAX SPARGO имеют выдающийся срок службы, а также отличную устойчивость в поле и при дорожных перевозках.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Опрыскиватель

| | |
|-----------|----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | VF 380/90 R 46 |
| LI/SS | 175 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94070206 |
| Section Width (inch) | 15.4 |
| Overall Diameter (inch) | 72.9 |
| Static Loaded Radius (inch) | 33.4 |
| Rolling Circumference (inch) | 219.8 |
| Rim Rec | DW 13 B |
| Rim Alt | W 13 A ; DW 12 |
| ECE | E11-106R-007527 |
| TRA Code | R1 |

Load capacity (lbs)

| mph / psi | 17 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 46 | 49 | 52 | 55 | 58 | 61 | 64 | 67 |
|---------------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 6250 | 7040 | 7690 | 8080 | 8470 | 8730 | 9000 | 9520 | 9910 | 10300 | 10700 | 11080 | 11350 | 11730 | 12000 | 12520 | 13040 | 13690 |
| From 40 to 25 | 6880 | 7740 | 8460 | 8890 | 9320 | 9610 | 9890 | 10470 | 10900 | 11330 | 11750 | 12180 | 12470 | 12900 | 13190 | 13760 | 14330 | 15220 |
| 20 | 7020 | 7900 | 8620 | 9070 | 9500 | 9790 | 10080 | 10660 | 11100 | 11550 | 11990 | 12430 | 12710 | 13150 | 13440 | 14030 | 14620 | 15520 |
| 12 | 7150 | 8050 | 8790 | 9240 | 9680 | 9980 | 10280 | 10870 | 11330 | 11780 | 12220 | 12670 | 12970 | 13410 | 13710 | 14300 | 14910 | 15830 |
| 5 | 7570 | 8510 | 9300 | 9770 | 10240 | 10560 | 10870 | 11500 | 11980 | 12450 | 12920 | 13400 | 13720 | 14190 | 14500 | 15130 | 15770 | 16740 |

Printed on 20.04.2024 17:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..