AGRIMAXFACTOR - Технические спецификации

Description

AGRIMAXFACTOR — новые шины компании BKT 70-й серии для тракторов, используемых для обработки почвы и грузовых перевозок. Улучшенный рисунок протектора с новой ориентацией грунтозацепов увеличенной высоты обеспечивает отличную проходимость. Уменьшенный угол расположения грунтозацепов способствует снижению сопротивления качению, а увеличенная на 5 % площадь контакта значительно сокращает уровень шума в кабине, что повышает комфорт оператора. Прочный каркас из специальных полиэфирных нитей гарантирует превосходную поперечную устойчивость и более быстрый отклик рулевого управления даже при высокой скорости выполнения рабочих операций или в тяжелых условиях эксплуатации. Шина гарантирует эффективное торможение даже на мокрой поверхности.
Основные преимущества AGRIMAXFACTOR: отличная управляемость в сочетании с во многом непревзойденным уровнем ездового комфорта, а также исключительная долговечность. Эта модель удовлетворяет всем требованиям крупногабаритной техники, в том числе оснащенной тяжелыми тяговыми аккумуляторными батареями электрического привода. На боковине шины нанесен логотип E-READY, который подчеркивает приверженность компании BKT электрической мобильности.

UM

US Standard

Construction

RADIAL

Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TL

Tyre Size	420/70 R 24
LI/SS	134 D/137 A8

Dimensions US Standard

Usa code	94070947
Section Width (inch)	16.5
Overall Diameter (inch)	49.1
Static Loaded Radius (inch)	22.2
Rolling Circumference (inch)	145.5
Rim Rec	W 13
Rim Alt	W 12 ; W 14 L
ECE	E11-106R-007641
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
40	2340	2710	3090	3510	3880	4250	4670
30	2460	2850	3250	3690	4090	4480	4920
25	2570	2980	3380	3850	4250	4670	5130
20	2690	3130	3560	4030	4480	4910	5380
5 LT	3140	3650	4140	4710	5210	5710	6270
5 HT	2690	3130	3560	4030	4480	4910	5380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 8:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..