AGRIMAXFACTOR - Технические спецификации

Description

AGRIMAXFACTOR — новые шины компании BKT 70-й серии для тракторов, используемых для обработки почвы и грузовых перевозок. Улучшенный рисунок протектора с новой ориентацией грунтозацепов увеличенной высоты обеспечивает отличную проходимость. Уменьшенный угол расположения грунтозацепов способствует снижению сопротивления качению, а увеличенная на 5 % площадь контакта значительно сокращает уровень шума в кабине, что повышает комфорт оператора. Прочный каркас из специальных полиэфирных нитей гарантирует превосходную поперечную устойчивость и более быстрый отклик рулевого управления даже при высокой скорости выполнения рабочих операций или в тяжелых условиях эксплуатации. Шина гарантирует эффективное торможение даже на мокрой поверхности.
Основные преимущества AGRIMAXFACTOR: отличная управляемость в сочетании с во многом непревзойденным уровнем ездового комфорта, а также исключительная долговечность. Эта модель удовлетворяет всем требованиям крупногабаритной техники, в том числе оснащенной тяжелыми тяговыми аккумуляторными батареями электрического привода. На боковине шины нанесен логотип E-READY, который подчеркивает приверженность компании BKT электрической мобильности.

UM

International Standard

Construction

RADIAL

Machinery

Сельское хозяйство: Трактор-тягач

Version	STANDARD
Type	TL

Tyre Size	620/70 R 42
LI/SS	160 D/163 A8

Dimensions International Standard

Section Width (mm)	625
Overall Diameter (mm)	1935
Static Loaded Radius (mm)	863
Rolling Circumference (mm)	5786
SRI (mm)	925
Rim Rec	DW 20 B
Rim Alt	DW18L ; W18L
ECE	E11-106R-007764
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	2475	2880	3285	3690	4095	4500
50	2600	3025	3450	3875	4300	4725
40	2715	3160	3600	4045	4490	4930
30	2850	3315	3780	4245	4710	5175
10 LT	3320	3860	4405	4945	5490	6030
10 HT	2850	3315	3780	4245	4710	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.10.2024 9:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..