

AIROMAX AM 27 - Технические спецификации



Description

Шины AIROMAX AM 27 предназначены для мобильных строительных кранов и идеально подходят для эксплуатации на дорогах. Они отличаются исключительной термостойкостью и обеспечивают непревзойденный комфорт при движении. Скоростные шины AIROMAX AM 27 подойдут для любой техники, от которой требуется высокий уровень управляемости.

UM

International Standard

Construction

 RADIAL

Machinery

Производство: Самоходный кран

| | |
|-----------|-----------------------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 385/95 R 24 (14.00 R 24) |
| LI/SS | 170 F |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Overall Width (mm) | 372 |
| Overall Diameter (mm) | 1363 |
| Static Loaded Radius (mm) | 626 |
| Rolling Circumference (mm) | 4175 |
| Rim Rec | 10.00W |
| ECE | E11-54R-0015910 |

Load capacity (Kg)

| km/h / bar | 9.00 |
|------------|------|
| 80 | 6000 |

Printed on 25.04.2024 7:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..