

## AIROMAX AM 27 - Технические спецификации



### Description

Шины AIROMAX AM 27 предназначены для мобильных строительных кранов и идеально подходят для эксплуатации на дорогах. Они отличаются исключительной термостойкостью и обеспечивают непревзойденный комфорт при движении. Скоростные шины AIROMAX AM 27 подойдут для любой техники, от которой требуется высокий уровень управляемости.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Производство: Самоходный кран

Version	STANDARD
Type	TL
Tyre Size	505/95 R 25 (18.00 R 25)
LI/SS	186 E

## Dimensions US Standard

Usa code	94045198
Overall Width (inch)	19.4
Overall Diameter (inch)	63
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	192.9
Rim Rec	13.00/2.5

## Load capacity (lbs)

mph / psi	130
20	27200
25	26000
30	24700
35	23500
43	20900
50	17200
55	14700
62	12600

Printed on 25.04.2024 10:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..