

## AIROMAX AM 543 - Технические спецификации



### Description

Шины AIROMAX AM 543 предназначены для мобильных строительных кранов. Они обладают великолепными тяговыми характеристиками и высокой устойчивостью. Поскольку шины для подъемных кранов подвергаются особым нагрузкам и используются в экстремальных условиях, AIROMAX AM 543 были специально разработаны для обеспечения отличной термостойкости. Кроме того, они подойдут для любой техники, от которой требуется высокий уровень управляемости.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Производство: Самоходный кран

Version	STANDARD
Type	TT
Tyre Size	385/95 R 24 (14.00 R 24)
LI/SS	170 E

## Dimensions International Standard

Overall Width (mm)	375
Overall Diameter (mm)	1355
Static Loaded Radius (mm)	627
Rolling Circumference (mm)	4156
Rim Rec	10.00W

## Load capacity (Kg)

km/h / bar	9.00
70	6000

Printed on 19.04.2024 16:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..