

## ARROW - Технические спецификации



### Description

Шины ARROW подходят для прицепов, используемых для перевозок. Это дорожная шина, которая отличается высокой ходимостью и длительным сроком службы. Шина ARROW характеризуется высокой грузоподъемностью, в том числе и на большой скорости. Пользователям, которым нужны повышенные характеристики, предлагается усиленная версия шины, изготовленная из особой резиновой смеси.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Прицеп

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	216
<b>Overall Diameter (mm)</b>	825
<b>Rim Rec</b>	6.00 G
<b>Rim Alt</b>	5.50 F

## Load capacity (Kg)

	km/h / bar	7.60
	100 LS	1600
	100 LD	1400

Printed on 23.04.2024 17:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..