

AS 2001 - Технические спецификации



Description

AS 2001 — это диагональные шины, которые идеально подходят для тракторов, предназначенных для возделывания почвы. Рисунок протектора обеспечивает отличные тяговые характеристики и способность к самоочищению. Шины AS 2001 изготовлены из специальной резиновой смеси, стойкой к порезам и разрывам, которая обеспечивает также высокую грузоподъемность.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Трактор-тягач

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 16.9 - 28 |
| LI/SS | 139 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94002726 |
| Ply Rating | 12 |
| Section Width (inch) | 16.9 |
| Overall Diameter (inch) | 55.9 |
| Static Loaded Radius (inch) | 25.6 |
| Rolling Circumference (inch) | 170 |
| Rim Rec | W 15 L |
| Rim Alt | W 14 L |
| ECE | E4-106R-002045 |
| TRA Code | R1 |

Load capacity (lbs)

| | | |
|--|-----------|------|
| | mph / psi | 36 |
| | 25 | 5360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09.12.2024 8:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..