

## AS 504 - Технические спецификации



### Description

AS 504 — это агропромышленные шины для техники, которая используется для обработки почвы, сельскохозяйственных и погрузочно-разгрузочных работ. Шины отличаются исключительными свойствами самоочистки и повышенным сцеплением с поверхностью и подходят для сельскохозяйственных прицепов, а также для телескопических погрузчиков. Шины AS 504 предлагаются в нескольких версиях, которые смогут удовлетворить самые разнообразные требования пользователей. Версия HD изготовлена из специальной резиновой смеси, устойчивой к порезам и разрывам, а специальная версия обладает усиленным каркасом, который обеспечивает увеличенный срок службы.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Телескопический погрузчик • Прицеп для полевых работ

Производство: Телескопический погрузчик

Version	STANDARD
Type	TT
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	290
Overall Diameter (mm)	867
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2540
SRI (mm)	410
Rim Rec	9.00
ECE	E11-106R-003510

## Load capacity (Kg)

	km/h / bar	4.80
	10 FR	3400
	25 FR	2890
	30 FR	2720
	40 FR	2430
	10 DW	2380
	25 DW	2025
	30 DW	1905
	40 DW	1700

Printed on 17.04.2024 4:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..