

AS 504 - Технические спецификации



Description

AS 504 — это агропромышленные шины для техники, которая используется для обработки почвы, сельскохозяйственных и погрузочно-разгрузочных работ. Шины отличаются исключительными свойствами самоочистки и повышенным сцеплением с поверхностью и подходят для сельскохозяйственных прицепов, а также для телескопических погрузчиков. Шины AS 504 предлагаются в нескольких версиях, которые смогут удовлетворить самые разнообразные требования пользователей. Версия HD изготовлена из специальной резиновой смеси, устойчивой к порезам и разрывам, а специальная версия обладает усиленным каркасом, который обеспечивает увеличенный срок службы.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Телескопический погрузчик • Прицеп для полевых работ

Производство: Телескопический погрузчик

Version	SPECIAL
Type	TL
Tyre Size	7.00 - 12
LI/SS DRIVE WHEEL	88 A8
LI/SS FREE ROLLING	100 A8

Dimensions US Standard

Usa code	94037308
Ply Rating	8
Section Width (inch)	7.4
Overall Diameter (inch)	26.9
Static Loaded Radius (inch)	12.2
Rolling Circumference (inch)	80.7
Rim Rec	4.5
ECE	E11-106R-003382

Load capacity (lbs)

mph / psi	48
5 FR	2470
15 FR	2090
20 FR	1970
25 FR	1760
5 DW	1730
15 DW	1470
20 DW	1380
25 DW	1230

Printed on 17.04.2024 5:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..