

AS 505 - Технические спецификации



Description

Шины AS 505 лучше всего подходят для прицепов и сельскохозяйственной техники, используемой для обработки почвы. Шины отличаются исключительными свойствами самоочистки и повышенным сцеплением с грунтовой поверхностью, особенно при движении по илистой или влажной почве. Шины также отличаются длительным сроком службы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Сельскохозяйственное оборудование •
Прицеп

Version	STANDARD
Type	TL
Tyre Size	6.5/80 - 15
LI/SS DRIVE WHEEL	92 A8
LI/SS FREE ROLLING	104 A8

Dimensions International Standard

Ply Rating	8
Section Width (mm)	171
Overall Diameter (mm)	695
Static Loaded Radius (mm)	325
Rolling Circumference (mm)	2106
Rim Rec	5.0
Rim Alt	4½ K ; 5 K ; 5 J
ECE	E4-106R-002660

Load capacity (Kg)

km/h / bar	4.80
10 FR	1260
25 FR	1070
30 FR	1010
40 FR	900
10 DW	880
25 DW	750
30 DW	705
40 DW	630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23.04.2025 17:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..