

AT 111 HD - Технические спецификации



Description

Спортивные шины AT 111 HD разработаны для гонок по бездорожью. Увеличенная глубина протектора и утолщенные боковины обеспечивают дополнительное сцепление с дорогой и улучшенное управление торможением вдобавок к исключительным тяговым характеристикам и регулированию высоких оборотов при торможении двигателем. Шины AT 111 HD также порадуют своим долгим сроком службы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: вездеход

Version	STANDARD
Type	TL
Tyre Size	AT 21 X 7 - 10
LI/SS	30 J

Dimensions International Standard

Ply Rating	6
Section Width (mm)	178
Overall Diameter (mm)	533
Rim Rec	5.5 AT
Rim Alt	6.0 AT
ECE	E4-75R-0006329

Load capacity (Kg)

km/h / bar	0.45
100	106

Printed on 26.04.2024 0:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..