

## AT 171 - Технические спецификации



### Description

Шины AT 171 были специально разработаны для тракторов, работающих на илистом грунте. Специальный направленный очень глубокий рисунок протектора обеспечивает превосходную тягу на мокрых и илистых поверхностях.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: вездеход • Трактор для езды по грязи

|           |                |
|-----------|----------------|
| Version   | STANDARD       |
| Type      | TL             |
| Tyre Size | AT 28 X 9 - 14 |
| LI/SS     | 77 A8 / 53 F   |

## Dimensions International Standard

|                       |      |
|-----------------------|------|
| Ply Rating            | 6    |
| Section Width (mm)    | 205  |
| Overall Diameter (mm) | 715  |
| Rim Rec               | W 7  |
| Rim Alt               | W 6  |
| TRA Code              | R1W+ |

## Load capacity (Kg)

|                     | km/h / bar | 1.40 | 1.00 |
|---------------------|------------|------|------|
| 40 MUD BOGGING      |            | 412  | -    |
| 80 MUD BOGGING      |            | 206  | -    |
| 40 CASUAL TRANSPORT |            | -    | 335  |
| 80 CASUAL TRANSPORT |            | -    | 170  |

Printed on 25.04.2024 15:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..