AT 621 - Технические спецификации

Description

Шины AT 621 подходят для экскаваторов-погрузчиков и компактных погрузчиков, используемых при проведении погрузочных и землеройных работ в сельском хозяйстве. Очень высокий рисунок протектора AT 621 гарантирует отличную устойчивость к порезам и увеличивает срок службы шин. Кроме того, эти шины BKT отличаются долговечностью и способностью к самоочищению.
Шины AT 621 предлагаются в нескольких версиях, которые смогут удовлетворить самые разнообразные требования пользователей.

UM

International Standard

Construction

BIAS

Machinery

Сельское хозяйство: Компактный погрузчик • Экскаватор-погрузчик
Производство: экскаватор-погрузчик • Погрузчик

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16
LI/SS	137 A6

Dimensions International Standard

Ply Rating	16
Section Width (mm)	260
Overall Diameter (mm)	925
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-005364

Load capacity (Kg)

km/h / bar	7.25
30	2300

Printed on 16.04.2024 23:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..