

AW 09 - Технические спецификации



Description

Шины AW 09 разработаны специально для сельскохозяйственной техники, пресс-подборщиков (объединенных в группу) и прицепов, используемых для обработки почвы, уборки сена и грузоперевозок. Они идеально подходят для современного земледелия и эксплуатации как на дороге, так и в условиях бездорожья. Усиленный каркас шины обеспечивает повышенную грузоподъемность и увеличенный срок службы. Шины AW 09 изготавливаются из специальной резиновой смеси, устойчивой к порезам и разрывам, что обеспечивает беспрецедентную устойчивость к воздействию пожнивных остатков.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик • Сенокосилка •
Сельскохозяйственное оборудование • Прицеп

Version	STANDARD
Type	TL
Tyre Size	380/55 - 17
LI/SS DRIVE WHEEL	128 A8
LI/SS FREE ROLLING	141 A8

Dimensions US Standard

Usa code	94038060
Section Width (inch)	15.4
Overall Diameter (inch)	33.5
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	98.1
Rim Rec	13.00
ECE	E4-106R-000380

Load capacity (lbs)

mph / psi	46
5 FR	7950
15 FR	6760
20 FR	6360
25 FR	5680
5 DW	5560
15 DW	4720
20 DW	4440
25 DW	3970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12.11.2024 11:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..