

AW 705 - Технические спецификации



Description

Шины AW 705 разработаны для сельскохозяйственной техники, прицепов и пресс-подборщиков, используемых для обработки почвы и грузовых перевозок. Они идеально подходят современным фермерским хозяйствам благодаря повышенной прочности и высокой грузоподъемности.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик •
Сельскохозяйственное оборудование • Прицеп

Version	STANDARD
Type	TT
Tyre Size	14.0/65 - 16
LI/SS FREE ROLLING	142 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	353
Overall Diameter (mm)	870
Static Loaded Radius (mm)	388
Rolling Circumference (mm)	2549
Rim Rec	11.0
ECE	E4-106R-001901

Load capacity (Kg)

	km/h / bar	4.00
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650

Printed on 24.04.2024 12:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..