

AW 708 - Технические спецификации



Description

Шины AW 708 разработаны специально для сельскохозяйственной техники, прицепов и пресс-подборщиков, используемых для обработки почвы и уборочных работ. Шины в версии «HD» выполнены с использованием специальной резиновой смеси, стойкой к порезам и разрывам.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик •
Сельскохозяйственное оборудование • Прицеп
Производство: Прицеп

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	149 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00

Load capacity (Kg)

km/h / bar	4.50
10 FR	4550
25 FR	3870
30 FR	3640
40 FR	3250

Printed on 23.04.2024 14:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..