

## AW 708 - Технические спецификации



### Description

Шины AW 708 разработаны специально для сельскохозяйственной техники, прицепов и пресс-подборщиков, используемых для обработки почвы и уборочных работ. Шины в версии «HD» выполнены с использованием специальной резиновой смеси, стойкой к порезам и разрывам.

### UM

International Standard

### Construction

 BIAS

### Machinery

Сельское хозяйство: Пресс-подборщик •  
Сельскохозяйственное оборудование • Прицеп  
Производство: Прицеп

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS FREE ROLLING	152 A8

## Dimensions International Standard

Ply Rating	16
Section Width (mm)	500
Overall Diameter (mm)	945
Static Loaded Radius (mm)	416
Rolling Circumference (mm)	2750
Rim Rec	16.00

## Load capacity (Kg)

km/h / bar	3.20
10 FR	4970
25 FR	4225
30 FR	3975
40 FR	3550

Printed on 23.04.2024 16:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..