

AW 708 - Технические спецификации



Description

Шины AW 708 разработаны специально для сельскохозяйственной техники, прицепов и пресс-подборщиков, используемых для обработки почвы и уборочных работ. Шины в версии «HD» выполнены с использованием специальной резиновой смеси, стойкой к порезам и разрывам.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик •
Сельскохозяйственное оборудование • Прицеп
Производство: Прицеп

Version	STANDARD
Type	TL
Tyre Size	500/50 - 17
LI/SS FREE ROLLING	152 A8

Dimensions US Standard

Usa code	94030996
Ply Rating	16
Section Width (inch)	19.7
Overall Diameter (inch)	37.2
Static Loaded Radius (inch)	16.4
Rolling Circumference (inch)	108.3
Rim Rec	16.00

Load capacity (lbs)

mph / psi	46
5 FR	10960
15 FR	9310
20 FR	8760
25 FR	7830

Printed on 23.04.2024 15:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..