

AW 708 - Технические спецификации



Description

Шины AW 708 разработаны специально для сельскохозяйственной техники, прицепов и пресс-подборщиков, используемых для обработки почвы и уборочных работ. Шины в версии «HD» выполнены с использованием специальной резиновой смеси, стойкой к порезам и разрывам.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Пресс-подборщик •
Сельскохозяйственное оборудование • Прицеп
Производство: Прицеп

Version	STANDARD
Type	TL
Tyre Size	500/65 - 17
LI/SS FREE ROLLING	160 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	525
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3135
Rim Rec	16.0
ECE	E11-106R-004549

Load capacity (Kg)

	km/h / bar	3.50
	10 FR	6300
	25 FR	5355
	30 FR	5040
	40 FR	4500

Printed on 23.04.2024 8:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..