

AW 711 - Технические спецификации



Description

AW 711 — это радиальные шины для сельскохозяйственной техники, специально разработанные для современного фермерского хозяйства. Они подходят для грузовых перевозок, уборки сена и обработки почвы. Благодаря особой резиновой смеси протектора шины AW 711 имеют более продолжительный срок службы независимо от того, на каких поверхностях они используются, — мягких или твердых. Низкое сопротивление качению во время движения по дороге способствует значительной экономии расхода топлива. Благодаря технологии VF шины AW 711 выдерживают высокую нагрузку при низком давлении.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Сенокосилка • Сельскохозяйственное оборудование

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	265/70 R 16.5 (10 R 16.5)
LI/SS	134 A8/B

Dimensions International Standard

Section Width (mm)	264
Overall Diameter (mm)	773
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2286
SRI (mm)	370
Rim Rec	8.25
ECE	E11-106R-002978

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
50	680	895	1085	1255	1445	1635	1760	1930	2120
40	680	895	1085	1255	1445	1635	1760	1930	2120
30	760	1000	1215	1405	1615	1830	1975	2165	2375
25	810	1065	1290	1490	1720	1945	2100	2300	2525
20	860	1125	1365	1580	1820	2060	2225	2435	2675
10	955	1250	1515	1755	2020	2290	2470	2705	2970

Printed on 08.12.2023 16:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..