

## AW 711 - Технические спецификации



### Description

AW 711 — это радиальные шины для сельскохозяйственной техники, специально разработанные для современного фермерского хозяйства. Они подходят для грузовых перевозок, уборки сена и обработки почвы. Благодаря особой резиновой смеси протектора шины AW 711 имеют более продолжительный срок службы независимо от того, на каких поверхностях они используются, — мягких или твердых. Низкое сопротивление качению во время движения по дороге способствует значительной экономии расхода топлива. Благодаря технологии VF шины AW 711 выдерживают высокую нагрузку при низком давлении.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Сенокосилка • Сельскохозяйственное оборудование

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 340/65 R 18
LI/SS	153 A8/B

## Dimensions US Standard

Usa code	94053476
Section Width (inch)	13
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	106.4
Rim Rec	W 11
ECE	E11-106R-002992

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
From 5 to 30 mph	2580	3380	4110	4750	5480	6210	6680	7330	8050

Printed on 26.04.2024 11:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..