

AW 711 - Технические спецификации



Description

AW 711 — это радиальные шины для сельскохозяйственной техники, специально разработанные для современного фермерского хозяйства. Они подходят для грузовых перевозок, уборки сена и обработки почвы. Благодаря особой резиновой смеси протектора шины AW 711 имеют более продолжительный срок службы независимо от того, на каких поверхностях они используются, — мягких или твердых. Низкое сопротивление качению во время движения по дороге способствует значительной экономии расхода топлива. Благодаря технологии VF шины AW 711 выдерживают высокую нагрузку при низком давлении.

UM

US Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Сенокосилка • Сельскохозяйственное оборудование

Version	STEEL BELTED
Type	TL
Tyre Size	VF 410/50 R 16.5
LI/SS	153 B

Dimensions US Standard

Usa code	94055814
Section Width (inch)	16.1
Overall Diameter (inch)	32.9
Static Loaded Radius (inch)	13.8
Rolling Circumference (inch)	98.9
Rim Rec	AG 11.75
ECE	E11-106R-005024

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	67
From 5 to 30 mph	2260	2970	3590	4170	4790	5430	5850	6420	7040	8050

Printed on 26.04.2024 7:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..