

AW 726 - Технические спецификации



Description

Шины AW 726 разработаны специально для прицепов, используемых для грузовых перевозок. Они отлично подходят для эксплуатации как на дорогах, так и за их пределами. Шины AW 726 отличаются превосходными дорожными характеристиками и свойствами самоочистения. Эти шины с блочным рисунком протектора обеспечивают увеличенный срок службы.

UM

US Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Прицеп

Version	ARAMID BELTED
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

Dimensions US Standard

Usa code	94064366
Ply Rating	14
Section Width (inch)	11.8
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	14.3
Rolling Circumference (inch)	99.6
Rim Rec	9.00

Load capacity (lbs)

mph / psi	70
5 FR	7500
15 FR	6370
20 FR	6000
25 FR	5360
5 DW	5250
15 DW	4460
20 DW	4200
25 DW	3750

Printed on 23.04.2024 14:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..