

AW 726 - Технические спецификации



Description

Шины AW 726 разработаны специально для прицепов, используемых для грузовых перевозок. Они отлично подходят для эксплуатации как на дорогах, так и за их пределами. Шины AW 726 отличаются превосходными дорожными характеристиками и свойствами самоочистения. Эти шины с блочным рисунком протектора обеспечивают увеличенный срок службы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Прицеп

Version	STEEL BELTED
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Ply Rating	14
Section Width (mm)	300
Overall Diameter (mm)	855
Static Loaded Radius (mm)	373
Rolling Circumference (mm)	2540
Rim Rec	9.00
ECE	E11-106R-006974

Load capacity (Kg)

	km/h / bar	4.80
	10 FR	3400
	25 FR	2890
	30 FR	2720
	40 FR	2430
	10 DW	2380
	25 DW	2025
	30 DW	1905
	40 DW	1700

Printed on 23.04.2024 11:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..