

AW 726 - Технические спецификации



Description

Шины AW 726 разработаны специально для прицепов, используемых для грузовых перевозок. Они отлично подходят для эксплуатации как на дорогах, так и за их пределами. Шины AW 726 отличаются превосходными дорожными характеристиками и свойствами самоочистения. Эти шины с блочным рисунком протектора обеспечивают увеличенный срок службы.

UM

International Standard

Construction

 BIAS

Machinery

Сельское хозяйство: Прицеп

| | |
|--------------------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 420/55 - 17 |
| LI/SS DRIVE WHEEL | 121 A8 |
| LI/SS FREE ROLLING | 133 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 415 |
| Overall Diameter (mm) | 890 |
| Static Loaded Radius (mm) | 392 |
| Rolling Circumference (mm) | 2584 |
| Rim Rec | 13.00 |
| ECE | E11-106R-005265 |

Load capacity (Kg)

| km/h / bar | 2.00 |
|------------|------|
| 10 FR | 2885 |
| 25 FR | 2450 |
| 30 FR | 2305 |
| 40 FR | 2060 |
| 10 DW | 2030 |
| 25 DW | 1725 |
| 30 DW | 1625 |
| 40 DW | 1450 |

Printed on 22.04.2024 11:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..