

AW 729 - Загрузить лист технических данных



Description

Шина AW 729 разработана специально для сельскохозяйственной техники, прицепов и пресс-подборщиков, используемых для обработки почвы, уборки сена и грузоперевозок. Благодаря закругленной плечевой зоне и рисунку протектора с тремя канавками по центру оборудование с такими шинами меньше уплотняет почву и не повреждает ее.

AW 729 — идеальная шина для современного сельского хозяйства, которая подходит для эксплуатации как на дорогах, так и за их пределами.

UM

US Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Пресс-подборщик •
Сельскохозяйственное оборудование • Прицеп

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
340/55 - 16 (13.0/55 - 16)	STANDARD	94066117	121 A8	133 A8		11.0		13.5	30.9	14.1	92.8	TL	E11-106R-006421
15.0/55 - 17	STANDARD	94065387	122 A8	134 A8	10	13.00	13 ; W 13	15.2	33.5	14.8	100.8	TL	E11-106R-006434
380/55 - 17	STANDARD	94074150	122 A8	134 A8	10	13.00	13 ; W 13	15.2	33.5	14.8	100.8	TL	E11-106R-008727
480/45 - 17	STANDARD	94068975	134 A8	146 A8		16.00		18.9	34.1	15.7	99.4	TL	E11-106R-006798
500/50 - 17	STANDARD	94067466	137 A8	149 A8		16.00		19.7	37.2	16.8	113.6	TL	E11-106R-006616

Printed on 23.04.2024 23:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..