

ВК 826 - Технические спецификации



Description

Шины ВК 826 разработаны специально для эксплуатации на прицепах, используемых для грузовых перевозок. Эти диагональные шины отличаются превосходными тяговыми характеристиками даже при больших нагрузках. Шины ВК 826 также доступны в «промышленной» версии («Industrial») с более высокой устойчивостью к порезам и разрывам, в таком варианте шины подойдут и для экскаваторов-погрузчиков.

UM

International Standard

Construction

❖ BIAS

Machinery

Сельское хозяйство: Прицеп

Производство: экскаватор-погрузчик • Прицеп

Version	TRACTOR TRAILER
Type	TT
Tyre Size	9.00 - 16
LI/SS	138 A8

Dimensions International Standard

Ply Rating	18
Section Width (mm)	265
Overall Diameter (mm)	925
Rim Rec	6.50 H
Rim Alt	6.00 G

Load capacity (Kg)

km/h / bar	7.60
30	2360

Printed on 26.04.2024 6:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..